# THE COMPLETE LIFT BROCHURE





www.masind.net



# WE LOVE ELEVATORS

THE INDEX

Introduction	01	
Home Lift	04	
Passenger Lift	14	
Hospital Lift	30	
Panoramic Lift	32	
Freight Lift	34	
Automobile Lift	38	
Dumbwaiter	40	





# INTRODUCTION

MAS is a well known name in the elevator industry.

# WHO WE ARE

# MAS Industries is export oriented company

specializing in the customized design, development, manufacturing and distribution of high technology lift solutions including complete lifts, lift components, parking systems escalator -travelators and lift spare parts.

Our export activity extends internationally in more than 20 countries including Europe, Asia, Middle East and Africa . MAS is a well organised Lift Manufacturer incorporating the critical functions of R & D and after sales service together with the functions of manufacturing, procurement, sales marketing and HR.

# MAS INDUSTRIES PVT. LTD.



#### 2019

SAP HANA was implemented to streamline the workflow & strengthen the systems

### 2018

Company moved its footsteps towards expansion of manufacturing business by acquiring 2000 sq.mtr factory

2017 Bangalore branch was established

#### 2016

Sheetmetal manufacturing plant with latest punching, laser & bending machine was setup

#### 2014

Hyderabad and Chennai Branches were established

#### 2011

Company specialised in the electronics segment for an elevator industry by launching varieties of COP, LOP, Display, PCB Borads

#### 2009

Company specialised in the electrical segment for an elevator industry by launching elevator control panels

#### 2007

Became first Indian company to achieve CE certification for Elevator Overspeed govenor & safety gear

#### 2003

MAS Industries Pvt Ltd was inaugurated by its founding members, among whom Mr Aslam Mukadam is the Chairman and Mr. Mahmood Kazi is the Managing Director.



# **OUR HISTORY**



# MAS INDUSTRIES PVT. LTD.

# HOME LIFT

89

65

43/

creating your comfort is our passion



# StarG Ultra Delux

# For A Perfect Duplex

Unique tailor-made design options to upgrade your space. StarG Delux provides convenience with a more sophisticated approach. This indirect acting hydraulic life is suitable for vertical transportation inside or outside a multi-storey residence.

GENERAL SPACE	Suspension	2:1
	Machine Room	MRL
TECH SPECIFICATIONS	Max Car Travel (m)	11
	Max no of Stops	4
	Max Car Speed (m/s)	0.5
	Rated Load (kg)	450
	Motor	Gearless
	Shaft Structure	Aluminium / Metal
	Cabin	Aluminium Designer
	Min Pit Depth	200
	Min Headroom	3200
	Max Car Entrance	3

# **ELEVATOR FEATURES & ADVANTAGES**

- Stopping accuracy Low noise levels Emergency evacuation
- Eco-design
- Scaffoldless installation
- Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

StarG Ultra Deluxcan be installed in multiple types of residential buildings with shaft pit and headroom limitations. It is also available with aluminium shaft construction.





Compact Hydraulic control panel with leading Italian Elevator technology which best suits for your modern home.



# GLASS CABIN



# PROPOSED MODEL

	StarG Ultra D	elux (Auto Telescopi	
Sr. No.	Car Inside	Shaft Size	Clear Opening
	(WxD) in mm	(WxD) in mm	(WxH) in mm
1	800x800	1710x1525	800x2000
2	900x900	1810×1575	800x2000
3	1000x1000	1910x1675	900x2000
4	1100x1100	2010x1725	900x2000

Cabin Wall - Glass + Designer Flooring - White Marble Finish Mirror - Not Applicable Car Operating Panel - Surface mounted Handrail - Not Applicable Lighting - Indirect Ventilation - Blower

# StarG Delux

# **ELEVATOR FEATURES & ADVANTAGES**

Stopping accuracy Low noise levels Emergency evacuation Eco-design Fast delivery



# Inside Story

StarG Deluxis Mas unique traction lift solution that complies with lifts Directive 2014/33/EU. Installation can be customised to any architectural need and design, even special and challenging projects. It is an elegent and, above all, truly convenient solution, allowing for perfect fitting within any existing or new building.

GENERAL SPACE	Suspension	2:1
	Machine Room	MRL
TECH SPECIFICATIONS	Max Car Travel (m)	14
	Max no of Stops	5
	Max Car Speed (m/s)	1
	Rated Load (kg)	450
	Motor	Gearless
	Shaft Structure	NA
	Cabin	Aluminium Designer
	Min Pit Depth	200
	Min Headroom	3200
	Max Car Entrance	3

# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

StarG Delux is the ideal solution for low pit and headroom shafts and it is available with aluminium or steel shaft construction.





Full length control panel which drive gearless machine very precisely and give noiseless operation that suits your sweet and calm living room.



# MAS TOUCH 01



# PROPOSED MODEL

	StarG Delu	x (Auto Telescopic D	oor)
Sr. No.	Car Inside	Shaft Size	Clear Opening
	(WxD) in mm	(WxD) in mm	(WxH) in mm
1	800x800	1600x1415	800x2000
2	900x900	1700x1465	800x2000
3	1000x1000	1800x1565	900x2000
4	1100x1100	1900x1615	900x2000

Cabin Wall - SS Hairline + Miror Flooring - Black Sparkle Granite Mirror - Centre panel Full Length Car Operating Panel - Surface mounted Handrail - Round Chrome Finish Lighting - Indirect + Direct Ventilation - Blower / Fan StarG Super

# **Balancing Nature**

Engineered to be different, the StarG Super lift provides a smooth and peaceful ride every time. Noise levels have been significantly reduced, so passengers relax in a quiet space away from the everyday choas.

7 7			
	GENERAL SPACE	Suspension	2:1
1.		Machine Room	MRL
2	TECH SPECIFICATIONS	Max Car Travel (m)	14
de la		Max no of Stops	5
		Max Car Speed (m/s)	1
		Rated Load (kg)	450
	and the second second	Motor	Gearless
		Shaft Structure	NA
		Cabin	SS Designer
		Min Pit Depth	200
		Min Headroom	3200
		- Max Car Entrance	3
2	Entre and	Ev - CP	Se 18 . 10
		1	

# ELEVATOR FEATURES & ADVANTAGES

Compact design

Stopping accuracy

Low noise levels

Emergency evacuation

Eco-design

Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

The belt type machine and coated steel belts do not need additional lubrication, eliminating lubrication-related storage, clean-up and disposal of hazardous waste.





Split Type control panel which occupies very less space that can be hide under your door panel. Very handy for commissioning.



# MAS TOUCH 02



# PROPOSED MODEL

S

	StarG Supe	er (Auto Telescopic D	oor)
Sr. No.	Car Inside	Shaft Size	Clear Opening
	(WxD) in mm	(WxD) in mm	(WxH) in mm
1	800x800	1482x1415	800x2000
2	900x900	1582x1465	800x2000
3	1000x1000	1682x1565	900x2000
4	1100x1100	1782x1615	900x2000

Cabin Wall - SS Hairline + Miror Flooring - Designer PVC Mirror - Designer Car Operating Panel - Surface mounted/ Full length Handrail - Round Chrome Finish Lighting - Indirect + Direct Ventilation - Blower / Fan

# **StarH Ultra Delux**

### Luxury Accepted

**GENERAL SE** 

**TECH SPECI** 

Deal for comfort and ease. StarH Ultra Delux Delux, designed and manufactured according to Machinery Directive 2006/42/EC, meets any need for transportation and mobility. A value for money solution that provides access inside or outside a multi-storey residence and guarantees safety and style.

PACE	Suspension	2:1
	Machine Room	Mini
ICATIONS	Max Car Travel (m)	10.5
	Max no of Stops	4
$ \rightarrow $	Max Car Speed (m/s)	0.5
	Rated Load (kg)	450
	Motor	Hydraulic
_	Shaft Structure	Aluminium / Metal
1000	Cabin	Aluminium Designer
	Min Pit Depth	150
	Min Headroom	2800
	Max Car Entrance	3

# **ELEVATOR FEATURES & ADVANTAGES**

Stopping accuracy Low noise levels Emergency evacuation Eco-design Scaffoldless installation Fast delivery



# MAS INDUSTRIES PVT. LTD.

#### \*\*\*\*

StarH Ultra Delux is the ideal solution for low pit and headroom shafts and it is available with aluminium shaft construction.





Hydraulic Controller design with the advance technology that completely suits with your luxurious home.



# GLASS CABIN



# PROPOSED MODEL

StarH Ultra Delux (Car sensor & Landing Swing Door)

Sr. No.	Car Inside	Shaft Size	Clear Opening
	(WxD) in mm	(WxD) in mm	(WxH) in mm
1	800x800	1300x1346	800x2000
2	900x900	1360x1452	800x2000
3	1000x1000	1480x1546	900x2000
4	1100x1100	1560x1646	900x2000
	StarH Ultra D	elux (Auto Telescopi	ic Door)
1	800x800	1580x1532	800x2000
2	900x900	1580x1632	800x2000
3	1000x1000	1730x1732	900x2000
4	1100x1100	1730x1832	900x2000
	-		

Cabin Wall - Glass + Designer Flooring - White Marble Finish Mirror - Not Applicable Car Operating Panel - Handrail COP Handrail - Round Chrome Finish Lighting - Indirect Ventilation - Blower

# StarH Delux

# The Style Quotient

StarH Delux is a hydraulic lifting system with very low energy consumption, ideal for private residences. Requiring only minimum space, the system is built to strict quality standards and features quick and easy installation. The option of aluminium shaft is available if required.

GENERAL SPACE	Suspension	2:1
	Machine Room	Mini
TECH SPECIFICATIONS	Max Car Travel (m)	10.5
	Max no of Stops	4
	Max Car Speed (m/s)	0.5
	Rated Load (kg)	450
	Motor	Hydraulic
	Shaft Structure	NA
	Cabin	Aluminium Designer
	Min Pit Depth	150
	Min Headroom	2800
	Max Car Entrance	3

# ELEVATOR FEATURES & ADVANTAGES

Stopping accuracy Low noise levels Emergency evacuation Eco-design Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

At MAS, we are sure that you will be pleasantly surprised at how affordable a reliable and stylish home lift can be. That is because MAS has designed Star Delux the most cost -effective home lift offered in today's market.





Controller panel accomplished with the high-end technology that simulate hydraulic pump very precisely to get world class ride comfort.



# MAS SILVER 01



# PROPOSED MODEL

StarH Delux (Car sensor & Landing Swing Door) Sr. No. Car Inside Shaft Size Clear Opening (WxD) in mm (WxD) in mm (WxH) in mm 800x800 1250x1233 800x2000 1 2 900x900 1250x1333 800x2000 3 1000x1000 1370x1433 900x2000 4 1100x1100 1450x1533 900x2000 StarH Delux (Auto Telescopic Door) 800x800 1470x1414 800x2000 2 900x900 1470x1514 800x2000 3 1000x1000 1620×1614 900x2000 4 1100x1100 1620x1714 900x2000

Cabin Wall - SS Mirror + Etching Flooring - White PVC Marble Finish Mirror - Not Applicable Car Operating Panel - Handrail COP Handrail - Hairline Finish Lighting - Indirect + Direct Ventilation - Blower / Fan www.masind.net

# MAS INDUSTRIES PVT. LTD.



# Galaxy Basic

# **ELEVATOR FEATURES & ADVANTAGES**

Mix & matach design Stopping accuracy Low noise levels - 52-54dB (A) Emergency evacuation Fast delivery

#### Machine Room MR Max Car Travel (m) 30 11 Max no of Stops Max Car Speed (m/s) 1 Rated Load (kg) 272-600 Motor Geared Shaft Structure NA Min Pit Depth 1500 Min Headroom(mm) 4250 2 Max car entrance Manual/Auto Door Type

# MAS INDUSTRIES PVT. LTD.

#### \*\*\*\*

Galaxy Basic is equipped with a state of the art inverter that minimies sound and ensures both outstanding ride quality and exceptioally low energy consumption.



1:1

# The Basic Affair

**GENERAL SPACE** 


**TECH SPECIFICATIONS** 

Galaxy Basic is a highly economical traction MRL solution for residential buildings. Serving rated loads of 375-1000kg, Galaxy Basic is designed to offer both reduced total cost of ownership (TCO) and value for money.

Suspension



Standard geared controller which take care complete safety of passenger and design for highly demanding mid-rise residential and commercial building.



### MAS ELEMENTAL 03



# PROPOSED MODEL

				Galaxy Basic	2		
				Car Collapsible Landing Manual Swing Door	Auto Telescopic Doors	(Auto Centre Opening Doors)	
Sr. No.	Passenger	Car Are	Car Inside	Shaft Size	Shaft Size	Shaft Size	Clear Opening
	Capacity	in sq.mm	(WxD) in mm	(WxD) in mm	(WxD) in mm	(WxD) in mm	(WxH) in mm
		min1.00	800x1250	1250X1675	1350X1825	1550x1750	700x2000
1	6	max1.10	1000x1100	1450X1525	1450X1675	1550x1600	
		min1.33	900x1500	1350X1915	1500X2075	1750x2000	800x2000
2	8	max1.44	1200×1200	1650X1625	1650X1775	1750x1700	

Flooring - Grey PVC Finish Mirror - Half Height Full Width Car Operating Panel - Surface mounted Handrail - Round Chrome Finish Lighting - Indirect + Direct Ventilation - Blower / Fan

Cabin Wall - MS Powder Coated

INDUSTRIES PVT. LTD

# Galaxy Modern

# Modern is Today

Galaxy Modern guarantees outstanding performance and exceptionally low energy consumption. The additional of Destination Control ensures passenger waiting times are significantly reduced.

ENERAL SPACE	Suspension	2:1
	Machine Room	MRL
ECH SPECIFICATIONS	Max Car Travel (m)	30
	Max no of Stops	11
	Max Car Speed (m/s)	1
//	Rated Load (kg)	272-600
Are the	Motor	Gearless
	Shaft Structure	NA
	Min Pit Depth	1500
	Min Headroom(mm)	4250
	Max car entrance	2
	Door Type	Auto

# ELEVATOR FEATURES & ADVANTAGES

Emergency evacuation Extra safety features Fast delivery



# MAS INDUSTRIES PVT. LTD.


\*\*\*\*

Galaxy Modern is equipped with a state of the art inverter that minimises sound and ensures both outstanding ride quality and exceptionally low energy consumption.





MRL controller design for high speed elevator up to 2m/s. Easy for installation and commissioning.



# MAS ELEMENTAL 01



# PROPOSED MODEL

	Galaxy Modern (Auto Telescopic Doors)					
Sr. No.	Passenger	Car Are	Car Inside	Shaft Size	Clear Opening	
	Capacity	in sq.mm	(WxD) in mm	(WxD) in mm	(WxH) in mm	
		min1.00	800x1250	1540x1650	700x2000	
1	6	max1.10	1000x1100	1740x1500		
		min1.33	900x1500	1660x1900	800x2000	
2	8	max1.44	1200x1200	1960x1600		
	Galax	y Moderr	n (Auto Centr	e Opening D	oors)	
1	6	min1.00	800x1250	1690x1570	700x2000	
		max1.10	1000x1100	1790x1420		
2	8	min1.33	900x1500	1860×1820	800x2000	
		max1.44	1200x1200	2010x1520		

Cabin Wall - MS Powder Coated Flooring - PVC Black Studded Finish Mirror - Centre panel Full Length Car Operating Panel - Surface mounted Handrail - Round Chrome Finish Lighting - Indirect + Direct Ventilation - Blower / Fan



### **Premium is Luxury**

Galaxy Premium provides a practical traction MRL option for commercial and public buildings. Designed to serve rated loads of up to 1000kg, Galaxy Premium can be adapted to accommodate your specific lift requirements, including specialist anti-vandal, firefighting lift solutions.

General Specs	Suspension	2:1
	Machine Room	MRL
Tech Specification	Max Car Travel (m)	45
	Max no of Stops	16
	Max Car Speed (m/s)	1.75
	Rated Load (kg)	272-1000
	Motor	Gearless
	Shaft Structure	NA
	Min Pit Depth	2150
	Min Headroom(mm)	4800
	Max car entrance	2
	Door Type	Auto

### **ELEVATOR FEATURES & ADVANTAGES**

Unique tailor-made design Stopping accuracy Extra safety features Vandal resistant lifts (EN81-71) Firefighting lifts (EN81-72) Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

Galaxy Premium guarantees outstanding performance and exceptionally low energy consumption. The additional feature of Destination Control ensures passenger waiting times are significantly reduced.





Integrated controller for your high-rise application up to 1.5m/s. Accomplished with direct landing feature that save the time and give best performance in heavy passenger traffic.



# MAS GOLD 01



# PROPOSED MODEL

Galaxy Premium (Auto Telescopic Doors)						
Sr. No.	Passenger	Car Are	Car Inside	Shaft Size	Clear Opening	
	Capacity	in sq.mm	(WxD) in mm	(WxD) in mm	(WxH) in mm	
		min1.60	900x1800	1640x2200	800x2000	
1	10	max1.76	1400x1250	2140x1650		
		min2.01	1000x2050	1800x2450	900x2000	
2	13	max2.20	1450x1525	2270x1920		
	Galaxy Premium (Auto Centre Opening Doors)					
1	10	min1.60	900x1800	1840x2100	800x2000	
		max1.76	1400x1250	2140x1550		
2	13	min2.01	1000x2050	2010x2380	900x2000	
		max2.20	1450x1525	2300x1850		

Cabin Wall - Gold Etching + Mirror Flooring - Black Granite Mirror - Designer Car Operating Panel - Vison Touch Panel Handrail - Not Applicable Lighting - Indirect + Direct Ventilation - Blower / Fan



# ELEVATOR FEATURES & ADVANTAGES

Reliability Spatial efficiency Extra safety features Vendal resistent lifts (EN81-71) Firefighting lifts (EN81-71) Fast delivery



# The Public Figure

Galaxy Rapid is the first choice for a range of commercial and public buildings operating rated loads of 1050-2500kg. Offering the option to install a larger car in a standard-sized shaft, Galaxy Rapid provides optimum space efficiency for buildings with high density passenger flow.

GENERAL SPACE	Suspension	2:1
	Machine Room	MRL
TECH SPECIFICATIONS	Max Car Travel (m)	75
	Max no of Stops	25
	Max Car Speed (m/s)	2
	Rated Load (kg)	375-1000
	Motor	Gearless
	Shaft Structure	NA
	Min Pit Depth	2200
	Min Headroom(mm)	5200
	Max car entrance	2
	Door Type	Auto

# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

Galaxy Rapid features premium quality gearless motor and is equipped with a state of the art inverter that provides outstanding ride quality and exceptionally low energy consumption and sound levels.





MRL controller design for high speed elevator up to 2m/s. Easy for installation and commissioning.







PROPOSED MODEL

	Galaxy Rapid (Auto Telescopic Doors)					
Sr. No.	Passenger	Car Are	Car Inside	Shaft Size	Clear Opening	
	Capacity	in sq.mm	(WxD) in mm	(WxD) in mm	(WxH) in mm	
		min2.27	1000x2275	1820x2670	900x2000	
1	15	max2.47	1600x1525	2420x1920		
		min2.88	1100x2625	1920x3025	1000x2000	
2	20	max3.13	1800x1725	2620x2230		
	Galc	ixy Rapid	(Auto Centre	e Opening Do	oors)	
1	6	min2.27	1000x2275	1950x2600	900x2000	
		max2.47	1600x1525	2420x1850		
2	8	min2.88	1100x2625	2070x2950	1000x2000	
		max3.13	1800x1725	2620x2160		

Cabin Wall - SS Hairline + Etching Flooring - Wooden Finish Mirror - Not Applicable Car Operating Panel - Full Length Panel Handrail - Curve Hairline Finish Lighting - Indirect + Direct Ventilation - Blower / Fan

# Galaxy Cooper

# The Space Story

Galaxy Cooper provides a practical traction MRL solution for residential buildings with pit and headroom limitations. Suitable for rated loads up to 1050kg, Galaxy cooper features premium quality gearless motor, 2:I suspension and speeds of up to Im/s. The state-of-the-art inverter minimises noise and delivers outstanding ride quality and exceptionally low energy consumption.

Suspension	2:1
Machine Room	MRL
Max Car Travel (m)	40
Max no of Stops	14
Max Car Speed (m/s)	1.7
Rated Load (kg)	300-1000
Motor	Gearless Belt
Shaft Structure	NA
Min Pit Depth	2150
Min Headroom(mm)	4800
Max car entrance	2
Door Type	Auto
	Machine Room Max Car Travel (m) Max no of Stops Max Car Speed (m/s) Rated Load (kg) Motor Shaft Structure Min Pit Depth Min Headroom(mm) Max car entrance

### **ELEVATOR FEATURES & ADVANTAGES**

C

Compact design World class design Spatial efficiency Safe door closing Emergency evacuation Fast delivery



# MAS INDUSTRIES PVT. LTD.


\*\*\*\*


Ideal for the modernisation of existing lifts and those with narrow shafts, Galaxy cooper strictly complies with lifts directive 2014/33/EC and standard EN81-21.





Split type control panel design to drive belt type motor which give the best ride quality in demanding elevator technology.





Gear Instantaneous or Progressive

Superior Quality Guide Rails with male-female joint

CE Certified Rope Tensioner with Switch 

# MAS TOUCH 03



# PROPOSED MODEL

#### Galaxy Cooper (Auto Telescopic Doors)

Passenger	Car Are	Car Inside	Shaft Size	Clear Opening		
Capacity	in sq.mm	(WxD) in mm	(WxD) in mm	(WxH) in mm		
	min1.00	800x1250	1400x1600	700x2000		
6	max1.10	1000x1100	1600x1500			
	min1.33	900x1500	1500x1850	800x2000		
8	max1.44	1200x1200	1800x1550			
Gala	ху Сооре	r (Auto Centi	e Opening D	oors)		
6	min1.00	800x1250	1550x1550	700x2000		
	max1.10	1000x1100	1650x1400			
8	min1.33	900x1500	1730x1800	800x2000		
	max1.44	1200x1200	1880x1500			
	Capacity 6 8 Gala 6	Capacity in sq.mm   min1.00 min1.00   6 max1.10   min1.33 max1.44   Galaxy Coope min1.00   6 min1.00   8 min1.00   8 min1.33	Capacity in sq.mm (WxD) in mm   min1.00 800x1250   6 max1.10 1000x1100   min1.33 900x1500   8 max1.44 1200x1200   Galaxy Cooper (Auto Centul) 6 min1.00 800x1250   6 min1.00 800x1250 max1.10 1000x1100   8 min1.33 900x1500 900x1500 900x1500	Capacity in sq.mm (WxD) in mm (WxD) in mm   min1.00 800x1250 1400x1600   6 max1.10 1000x1100 1600x1500   min1.33 900x1500 1500x1850   8 max1.44 1200x1200 1800x1550   Galaxy Cooper (Auto Centre Opening D 6 min1.00 800x1250   6 min1.01 1000x1100 1650x1400   8 min1.33 900x1500 1730x1800	Capacity in sq.mm (WxD) in mm (WxD) in mm (WxH) in mm   min1.00 800x1250 1400x1600 700x2000   6 max1.10 1000x1100 1600x1500   min1.33 900x1500 1500x1850 800x2000   8 max1.44 1200x1200 1800x1550 Galaxy Cooper (Auto Centre Opening Doors)   6 min1.00 800x1250 1550x1550 700x2000   8 min1.01 1000x1100 1650x1400 800x2000	Capacity in sq.mm (WxD) in mm (WxD) in mm (WxH) in mm   min1.00 800x1250 1400x1600 700x2000   6 max1.10 1000x1100 1600x1500   min1.33 900x1500 1500x1850 800x2000   8 max1.44 1200x1200 1800x1550   Galaxy Cooper (Auto Centre Opening Doors) 6 min1.00 800x1250   6 min1.00 800x1250 1550x1550 700x2000   8 min1.33 900x1500 1730x1800 800x2000

Cabin Wall - SS Hairline + Miror Flooring - Black Granite Finish Mirror - Designer Car Operating Panel - Surface mounted Handrail - Bar Hairline + Mirror Finish Lighting - Indirect + Direct Ventilation - Blower / Fan

# Galaxy CTL

# See All Sides

Galaxy CTL is the ideal traction MRL solution for commercial and public buildings. Serving rated loads of up to 1000kg, Galaxy CTL is built to high technical specifications and is specifically designed to support the installation of up to three cabin doors and a cantilever car frame.

GENERAL SPACE		
	Suspension	2:1
	Machine Room	MRL
ECH SPECIFICATIONS		
	Max Car Travel (m)	24
	Max no of Stops	8
	Max Car Speed (m/s)	1
	Rated Load (kg)	272-1000
	Motor	Geared/Gearless
	Shaft Structure	NA/Optional
	Min Pit Depth	1500
	Min Headroom(mm)	4250
	Max car entrance	3
	Door Type	Manual/Auto

# ELEVATOR FEATURES & ADVANTAGES

World class design

Emergency evacuation

Eco-friendly

Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

Featuring a range of customisable design solutions, Galaxy CTI, is the first choice for panoramic lifts.





MRL controller panel. Accomplished with Japanese and Italian technology which gives best and safe ride quality for the passenger



# MAS SILVER 03



# PROPOSED MODEL

	Galaxy CTL (Auto Telescopic Doors)					
Sr. No.	Passenger	Car Are	Car Inside	Shaft Size	Clear Opening	
	Capacity	in sq.mm	(WxD) in mm	(WxD) in mm	(WxH) in mm	
		min1.00	800x1250	1550x1650	700x2000	
1	6	max1.10	1000x1100	1750x1600		
		min1.33	900x1500	1650x1850	800x2000	
2	8	max1.44	1200x1200	1950x1600		
	Gal	axy CTL (A	Auto Centre (	Opening Doo	rs)	
1	6	min1.00	800x1250	1800x1560	700x2000	
		max1.10	1000x1100	1600×1915		
2	8	min1.33	900x1500	1950x1800	800x2000	
		max1.44	1200x1200	1800x2015		

Cabin Wall - SS Mirror + Etching Flooring - Designer Marble Finish Mirror - Designer Car Operating Panel - Flush Type Panel Handrail - Not Applicable Lighting - Indirect + Direct Ventilation - Blower / Fan

# HYDE - R

# The Refreshing Tool

Hyde-R indirect acting hydraulic lift is ideal for existing or new residential buildings that have pit and headroom limitations. The option of a small cabinet for the power unit and controller enables installation in shafts with or without a machine room.

GENERAL SPACE	Suspension	1:2
	Machine Room	Hydraulic
TECH SPECIFICATIONS	Max Car Travel (m)	18
	Max no of Stops	7
	Max Car Speed (m/s)	0.5
	Rated Load (kg)	272-1000
	Motor	Hydraulic
	Shaft Structure	NA/Optional
	Min Pit Depth	1350
	Min Headroom(mm)	4000
	Max car entrance	2
	Door Type	Manual/Auto

# **ELEVATOR FEATURES & ADVANTAGES**

Customized solution Spatial efficiency

Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### $\star\star\star\star\star$

Hyde-R is a cost-effective, eco-friendly and versatile lift solution that can be adapted to fit.





Standard hydraulic controller which accomplished with all kind of passenger safest and maintain floor level of car in all situation.



### MAS ELEMENTAL 02



# PROPOSED MODEL

				Hyde - R			
				Car Collapsible Landing Manual Swing Door	Auto Telescopic Doors	(Auto Centre Opening Doors)	
Sr. No.	Passenger	Car Are	Car Inside	Shaft Size	Shaft Size	Shaft Size	Clear Opening
	Capacity	in sq.mm	(WxD) in mm	(WxD) in mm	(WxD) in mm	(WxD) in mm	(WxH) in mm
		min1.00	800x1250	1300x1470	1550x1650	1550x1570	700x2000
1	6	max1.10	1000x1100	1480x1340	1460x1490	1610x1420	
		min1.33	900x1500	1400x1740	1380x1500	1750x1820	800x2000
2	8	max1.44	1200×1200	1660x1440	1590×1690	1810x1520	

Flooring - PVC Black Studded Finish Mirror - Designer Car Operating Panel - Surface mounted Handrail - Round Chrome Finish Lighting - Indirect + Direct Ventilation - Blower / Fan

Cabin Wall - MS Powder Coated

INDUSTRIES FVT. EFE

# Galaxy Wellness

### Wellness Forever

**GENERAL S** 

**TECH SPECIE** 

Galaxy Wellness is a practical traction MRL solutions for hospitals. Serving rated loads of up to 1000kg, Atlas Premium is a shaft, Featuring automated emergency evacuation capabilities, Galaxy Wellness provides peace of mind for the traveller.

PACE		
	Suspension	2:1
	Machine Room	MR/MRL
FICATIONS		
	Max Car Travel (m)	45
	Max no of Stops	16
	Max Car Speed (m/s)	1.75
	Rated Load (kg)	800-1500
	Motor	Geared/Gearless
	Shaft Structure	NA
	Min Pit Depth	2150
	Min Headroom(mm)	4800
	Max car entrance	2
	Door Type	

# ELEVATOR FEATURES & ADVAN

CES

Low noise levels Spatial efficiency Emergency alarm call manager Emergency evacuation Eco-design Fast delivery



6.0

# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

Passenger can enjoy seamless, stress free travel and reduced waiting times with the additional feature of Destination Control, Outstanding performance and exceptionally low energy consumption are garenteed.





Safe and reliable controller design which gives the best performance in high demanding environment of patient transportation.



# HOSPITAL LIFT CABIN



# PROPOSED MODEL

Galaxy Wellness (Auto Telescopic Door)						
Sr. No.	r. No. Passenger Car Inside Shaft Size C					
	Capacity	(WxD) in mm	(WxD) in mm	(WxH) in mm		
1	15	1000x2400	1800x2775	800x2000		
2	20	1300x2400	2250x2775	1200x2000		
3	26	1400x2750	2350x3125	1200x2000		

Cabin Wall - SS Hairline Flooring - Aluminium Chequer Plate Mirror - Half Height Full Width Car Operating Panel - Full Length Panel Handrail - Not Applicable Lighting - Indirect + Direct Ventilation - Blower / Fan

# Pancube / Pancurve

# When View is Important

We design Square, semi-circular or completely circular, our panoramic cabins are prefectly covering the most demanding design requirements.

Due to the enormous flexibility in choosing forms and materials, each panaromic cabin is always designed and contructed in absolute harmony with the architectural style of each building.

#### **GENERAL SPACE**

Suspension	2:1
Machine Room	MRL
Max Car Travel (m)	24
Max no of Stops	8
Max Car Speed (m/s)	1
Rated Load (kg)	272-1000
Motor	Gearless
Shaft Structure	NA
Min Pit Depth	1500
Min Headroom(mm)	4500
Max car entrance	1
Door Type	

ELEVATOR FEATURES & ADVANTAGES

World class design

Emergency evacuation

Eco-design

Fasticalivery





#### \*\*\*\*


This way the cabin is being upgraded from a simple means of transportation, to an architectural element. A real "ornament", ideal for luxury stores, shopping malls and modern residences.



TECH SPECIFICATIONS



Stylish controller design which best suits for your modern panoramic elevator and give most comfortable ride quality. Design to showcase your commercial complex, prestigious hotels and shopping centre.



2:1 Roping

Wide range of Cabins to choose from

Superior Quality Guide Rails with male-female joint



# PANAROMIC CABIN



# PROPOSED MODEL

Sr. No.	Passenger	Car Inside	Shaft Size	Clear Opening
	Capacity	(WxD) in mm	(WxD) in mm	(WxH) in mm
1	6	1100x1100	2050x1850	800x2000
2	8	1400x1100	2250x1900	800x2000
3	10	1400x1350	2250x1950	800x2000
4	13	1500x1550	2350x2150	900x2000
	Pana	curve (Auto Cen	tre Opening Do	ors)
1	8	1100x1600	2200x2185	800x2000
2	10	1200x1800	2300x2355	800x2000
3	13	1300x1950	2400x2535	900x2000

Cabin Wall - Glass + Designer Flooring - White Marble Finish Mirror - Not Applicable Car Operating Panel - Full Length Panel Handrail - Not Applicable Lighting - Indirect + Direct Ventilation - Blower / Fan

# Galaxy Jumbo

# The Body Builder

Fully compliment with Machinery Directive 2006/42/EC, Galaxy Jumbo is a dependable worrking tool, characterised by its reliable performance and endurance under harsh working conditions. You create the specifications for your Galaxy Jumbo. Flexible production enables us to meet your individual requirements with ease.

RAL SPACE	Suspension	2:1
	Machine Room	MR/MRL
SPECIFICATIONS	Max Car Travel (m)	45
	Max no of Stops	16
>	Max Car Speed (m/s)	1
	Rated Load (kg)	500-3000
	Motor	Gearless
	Shaft Structure	NA
	Min Pit Depth	1500
	Min Headroom(mm)	3450
	Max car entrance	2
	Door Type	

### **ELEVATOR FEATURES & ADVANTAGES**

**Rodust construction** 

Spatial efficiency

Customised solution

Fast delivery



# MAS INDUSTRIES PVT. LTD.

#### \*\*\*\*


GEN

Galaxy Jumbo is a hydraulic hoisting lift for freight, designed primarily for industrial facilities and warehouses, with no requirements for separate machine room.





Energy Saving, inverter-based freight elevator which take care of your heavy vertical transport in warehouse, store, Shop, restaurant, etc.



### FREIGHT LIFT CABIN



# PROPOSED MODEL

Galaxy Jumbo (Car & Landing Manual Collapsible Door)

Sr. No.	Rate Load	Car Inside	Shaft Size	Clear Opening	
	Kgs (WxD) in mm		(WxD) in mm	(WxH) in mm	
1	500	1200x1100	1960x1370	1100x2000	
2	1000	1600x1575	2420x1850	1400x2000	
3	1500	1900x1800	x1800 2720x2080	1700x2000	
4	2000	2100x2025	100x2025 2920x2300		
Galaxy Jumbo (Auto Telescopic Door)					
1 500		1200x1100	1960x1580	1100x2000	
2	1000	1600x1575	2420x1970	1400x2000	
		1900x1800	2720x2290	1700x2000	
		2100x2025	2920x2510	1700x2000	

# Hyde - F

# The Tough Guy

Fully compliant with Machinary Directive 2006/42/EC, HYDE-F is a dependable working tool, characterised by its reliable performance and endurance under harsh working conditions. You create the specifications for your HYDE-F. Flexible production enables us to meet your individual requirements with ease.

ENERAL SPACE	Suspension	1:2
	Machine Room	Hydraulic
H SPECIFICATIONS	Max Car Travel (m)	18
	Max no of Stops	7
$\rightarrow$	Max Car Speed (m/s)	0.5
	Rated Load (kg)	500-3000
	Motor	Hydraulic
	Shaft Structure	NA
	Min Pit Depth	1350
	Min Headroom(mm)	4000
	Max car entrance	2
	Door Type	

### **ELEVATOR FEATURES & ADVANTAGES**

Robust construction Spatial efficiency Customised solution Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

HYDE-F is a hydraulic hoisting lift for freight, designed primarily facilities and warehouses, with no requirements for separate machine room.






Hydraulic Freight elevator design to do complex transport task in warehouse, shopping centre or industrial facilities.



# FREIGHT LIFT CABIN



# PROPOSED MODEL

	Hyde-F (Car & Landing Manual Collapsible Door)						
Sr. No.	Rate Load	Car Inside	Shaft Size	Clear Opening			
	Kgs	(WxD) in mm	(WxD) in mm	(WxH) in mm			
1	500	1200x1100	1760x1370	1100x2000			
2	1000	1600x1575	2140x1855	1400x2000			
3	1500	1550x2200	2290x2480	1700x2000			
4	2000	1925x2200	2670x2480	1700x2000			
		Hyde-F (Auto 1	Telescopic Door)				
1	500	1200x1100	2080x1480	1100x2000			
2	1000		2250x1975	1400x2000			
3	1500	1550x2200	2700x2600	1700x2000			
4	2000	1925x2200	2700x2600	1700x2000			

37

# Automob T & H

# Personal Care

GENE

TECH

You can be assured of a safe entrance and exit of the vehicles, to the significant benefits of Mas Car lifts. Their construction is thought out to the smallest detail, and they are winning the best impressions since they are installed in busy private and public parking areas, continuously transporting every vehicles with outmost safety.

Ens-		Т	H
RAL SPACE -	Suspension	2:1/4:1	2:1
RAL SPACE	Machine Room	MR/MRL	Hydraulic
SPECIFICATIONS	Max Car Travel (m)	24	18
	Max no of Stops	8	7
	Max Car Speed (m/s)	1	0.5
	Rated Load (kg)	2500-3000	2500-3000
	Motor	Geared/Gearless	Hydraulic
. 600 800	Shaft Structure	NA	NA
	Min Pit Depth	1500	1500
	Min Headroom(mm)	5500	5500
	Max car entrance	2	2
	Door Type		

# ELEVATOR FEATURES & ADVANTAGES

Stiffness

Safety

Reliability

Aesthetics

Ease of installation



# MAS INDUSTRIES PVT. LTD.


### \*\*\*\*

MAS car - hydraulic and traction - are forged in order to withstand every hardship, satisfying even the most demanding requirements of functionality.






Robust and rigid design for carrying heavy item like machinery and Car safely to the destination.



# AUTOMOBILE LIFT CABIN



PROPOSED M	IODEL
	Automob - U (Poth Sido

Sr. No.	Rated Load	Car Inside	Shaft Size for 4 Panel	Shaft Size for 6 Panel	Clear Opening
	Kgs	(WxD) in mm	Verical Doors	Centre Opening Doors	(WxH) in mm
1		2600x5600	(WxD) in mm	(WxD) in mm	2600x2600
2		2500x5600	3300x6460	3700x6200	2500x2500
3	3000	2400x5600	3200x6460	3550x6200	2400x2400
4	1	2300x5300	3100x6460	3400x6200	2300x2300
5		2200x5200	3000x6160	3300x5900	2200x2200
		Auto	mob - T (Both Side		
1		2600x5600	3650x6460	3775x6200	2600x2600
2	-	2500x5600	3550x6460	3675x6200	2500x2500
3		2400x5600	3450x6460	3575x6200	2400x2400
4		2300x5300	3350x6100	3475x5900	2300x2300
5		2200x5200	3250x6000	3375x5800	2200x2200



# The Smart Guy

MAS Dumbwaiter is a small frieghts traction MRL lift. It is the ideal partner for lifting lightweight goods such as clothes, food, papers and other items. An excellent choice for both commercial and residential usage, the Dumbwaiter offers convenience and style to resturants, cafes, shops, warehouses, offices, hotels, houses, flats and other property types.

GENERAL SPACE	Suspension	1:1
	Machine Room	MR/MRL
TECH SPECIFICATIONS	Max Car Travel (m)	40
	Max no of Stops	12
	Max Car Speed (m/s)	0.15-0.6
	Rated Load (kg)	25-300
	Motor	Drum/Geared
	Shaft Structure	NA/Optional
	Min Pit Depth	600
	Min Headroom( mm )	1600
	Max Car Entrance	3
	Door Type	

ELEVATOR FEATURES & ADVANTAGES

Robust construction Spatial efficiency

**Customised solution** 

Fast delivery



# MAS INDUSTRIES PVT. LTD.


#### \*\*\*\*

MAS Dumbwaiter complies with European legislation (EN 81-3) and can be supplied with a 'self-supporting' steel frame if a concrete shaft is not available.






An economic design with average load capacity which carry your object safely to the destination.



# DUMBWAITER CABIN




Cabin Wall - SS Hairline Flooring - SS Hairline Mirror - Not Applicable Car Operating Panel - Not Applicable Handrail - Not Applicable Lighting - Indirect + Direct Ventilation - Not Applicable

Dumbwaiter (Manual Ve	ertical Bi-parting	Door)	ł

Sr. No.	Rate Load	Car Inside	Shaft Size	Clear Opening
1	Kgs	(WxD) in mm	(WxD) in mm	(WxH) in mm
2	200	900x1000	1400x1400	700x1200
3	250	1000x1200	1500x1550	700x1200

# 41



# MAS INDUSTRIES PRIVATE LIMITED

D-378,TTC Industrial estate, Turbhe MIDC, Navi Mumbai - 400705, India. PH: 022-27670174 / 5 / 6 Website - www.masind.net, Email : info@masind.net

# THE **COMPLETE LIFT** BROCHURE